

inView Video Verified



Rapid installation and fully power-independent, this high-spec Video-Verified Alarm system will detect movement via multiple sensors and send a short video clip via the mobile network to any location

Specifications : inView Video Verified

Indoor and outdoor PIR camera sensors with day/night visibility, and completely wire-free. Battery life for all devices and control panel is up to 4 years

Technical Information

Dimensions	130mm x 102mm x 141mm (approx.)
Material	Polycarbonate UL94
Power requirements	Battery type C Lithium batteries 3.6v LS14500
Radio type	Spread spectrum bidirectional
Radio frequency	868MHz
Transmission security	AES encryption algorithm
Alerts	Radio, batteries, tamper, position
Radio antenna	Integrated
Operating temperature	External: -20C to +60C / Internal: -10C to +55C
Mounting height	2m to 4m (approx.)
Mounting angle	5° to 10° (external)
Camera view angle	External: 110° / Internal: 90°
Detection range:	External: 18m / Internal: 12m (at 2m mount height)
Sensor type	CMOS
Daylight video	Programmable: colour or black & white
Night video	Automatic black & white infrared
Infrared illumination	External: up to 12m / Internal: up to 7m
Video format	MJPEG-WMV, MJPEG-DIFF
Video frame rate	5 images per second
Video duration	Programmable (10 seconds by default)
Video resolution	QVGA (320x240)
Video quality	SQ or HQ
Average video file size	220K
Image format	JPEG
Image resolution	VGA (640px x 480px)
Image quality	HQ or SQ
Average image file size	8 Kb
Approvals	External: CE NF EN50131-2-2 Internal: CE / EN50131 / NF&A2P



External camera sensor



Internal camera sensor

To find out how we can help you

Call: **01322 479652** or visit **www.clearway.co.uk**

clearway
BUILDING SECURITY & SUPPORT

Clearway Environmental Services (UK) Ltd.
Fountain House, Anchor Boulevard, Crossways Business Park,
Dartford, Kent DA2 6QH