

Solo Alarm MK 4



The Clearway Solo Alarm is a robust stand alone, battery powered, wire-free, alarm system designed for internal use where no mains power or telephone lines are available

Specifications : Solo Alarm MK 4

Specifically designed for use on vacant commercial and residential properties, this unique multi-sensor alarm system can be fitted, commissioned, verified and working to protect your property within 20 minutes

Technical Information	
Monitoring	Monitored by NSI, gold accredited, category BS5979 monitoring centre
Display	Integrated two-line recessed, vandal resistant, backlit LCD
Keypad	1,000,000 presses, single button Arm, vandal resistant keypad
Siren	Internal 112dB
Flashing dome	Cast moulded ABS (vandal resistant) with integrated blue flash
Batteries	Integrated 12v, 72AH, 3 year operational life
Sensors	PIR movement detector built-in: 2.5m x 8m range Multiple remote sensors (optional) Smoke (optional)
Voice module	Built in voice prompts to aid accessibility
Feedback	Built in buzzer provides audible feedback of alarm set, unset and fault conditions
Status indicators	Alarm status indicators for armed and disarmed states
Communications	Integrated roaming GSM modem with on-board diagnostics
Clock	Battery backed clock, time stamp
Operating temperature	-25C to +55C
Bell box	External (optional)
Tampers	Internal shock detector, case opening
Alarm functions	Multiple 4 digit PIN codes for simple, keyless access Daily access pin code Walk test Guard tour Lone worker protection Up to 10 channels Up to 256 sensors per channel Individual channel and sensor control Energy saving sleep modes Tamper still active when disarmed Intelligent false alert reduction and management Multi zone alert detection Adjustable entry & exit timer Commission and decommission functions Scheduled heartbeat reporting alarm system health Configurable sensor heartbeat intervals Configurable 'double knock' technology Internal event log for 512 events Export internal log to PC (adapter & software required)
Fixings	Wall mount, floor mount, free standing
Case material	Steel
Weight	15 kg (with batteries)
Dimensions	Height 410mm x Width 210mm x Depth 180mm
Environmental Classification	Environmental Class III, outdoor sheltered or indoor extreme



To find out how we can help you

Call: **01322 479652** or visit **www.clearway.co.uk**

clearway
BUILDING SECURITY & SUPPORT

Clearway Environmental Services (UK) Ltd.
Fountain House, Anchor Boulevard, Crossways Business Park,
Dartford, Kent DA2 6QH